

## SAFETY DATA SHEET

Fugen REINIGER 220 ml Farblos

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

**Product name** : Fugen REINIGER 220 ml Farblos

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Consumer use

Uses advised against

None

**Product use** : Use in accordance with directions on the can.

#### 1.3 Details of the supplier of the safety data sheet

Akzo Nobel Coatings GmbH Aubergstrasse 7 A-5161 Elixhausen

Telefon: +43 (0)810 / 500 129 Telefax: +43 (0)662 / 489 89 11

www.molto.at

e-mail address of person : sdbinfo@akzonobel.com responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Center

**Telephone number** : +43 1 406 43 43

Date of issue/Date of revision: 26-1-2024Version: 1Date of previous issue: 26-1-20241/16

Fugen REINIGER 220 ml Farblos

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Dam. 1, H318

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :

Signal word : Danger

**Hazard statements** : H318 - Causes serious eye damage.

**Precautionary statements** 

**General**: P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

**Prevention**: P280 - Wear eye or face protection.

Response : P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

: This mixture does not contain any substances that are assessed to be a PBT or a

Immediately call a POISON CENTER or doctor.

Storage : Not applicable.

Disposal : Not applicable.

Hazardous ingredients : sodium etasulfate

Supplemental label

elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

: Not applicable.

Special packaging requirements

Containers to be fitted

with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according

ıng

to Regulation (EC) No. 1907/2006, Annex XIII

: None known.

vPvB.

Other hazards which do not result in classification

Date of issue/Date of revision : 26-1-2024 Version : 1

Date of previous issue : 26-1-2024 2/16 AkzoNobel

Fugen REINIGER 220 ml Farblos

### **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
tetrapotassium pyrophosphate	EC: 230-785-7 CAS: 7320-34-5	≤5	Eye Irrit. 2, H319	-	[1]
sodium etasulfate	EC: 204-812-8 CAS: 126-92-1	≤5	Skin Irrit. 2, H315 Eye Dam. 1, H318	-	[1]
trisodium nitrilotriacetate	EC: 225-768-6 CAS: 5064-31-3 Index: 607-620-00-6	≤0.3	Acute Tox. 4, H302 Eye Irrit. 2, H319 Carc. 2, H351	ATE [Oral] = 500 mg/kg Carc. 2, H351: C ≥ 5%	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a physical, health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Date of issue/Date of revision : 26-1-2024 Version : 1

Date of previous issue : 26-1-2024 3/16 AkzoNobel

Fugen REINIGER 220 ml Farblos

#### **SECTION 4: First aid measures**

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### **Protection of first-aiders**

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion**: Adverse symptoms may include the following:

stomach pains

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst.

Date of issue/Date of revision: 26-1-2024Version: 1Date of previous issue: 26-1-20244/16AkzoNobel

Fugen REINIGER 220 ml Farblos

### SECTION 5: Firefighting measures

Hazardous combustion products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides phosphorus oxides metal oxide/oxides

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Contaminated absorbent material may pose the same hazard as the spilled product.

**AkzoNobel** 

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Date of issue/Date of revision Version :1 : 26-1-2024 Date of previous issue : 26-1-2024 5/16

Fugen REINIGER 220 ml Farblos

### SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

#### 7.1 Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

Recommendations : Not available.
Industrial sector specific : Not available.
solutions

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
No exposure limit value known.	

## Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Date of issue/Date of revision: 26-1-2024Version: 1Date of previous issue: 26-1-20246/16AkzoNobel

Fugen REINIGER 220 ml Farblos

### **SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Type	Exposure	Value	Population	Effects
tetrapotassium pyrophosphate	DNEL	Long term Inhalation	4.35 mg/m³	General population	Systemic
	DNEL	Long term	17.63 mg/ m³	Workers	Systemic
sodium etasulfate	DNEL	Long term Oral	24 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	85 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	285 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	2440 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	4060 mg/ kg bw/day	Workers	Systemic
trisodium nitrilotriacetate	DNEL	Long term Oral	0.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.8 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	1.75 mg/m³		Systemic
	DNEL	Long term Inhalation	3.2 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	5.25 mg/m³	Workers	Systemic

#### **PNECs**

No PNECs available.

#### 8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

#### Skin protection

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Date of issue/Date of revision: 26-1-2024Version: 1Date of previous issue: 26-1-20247/16AkzoNobel

Fugen REINIGER 220 ml Farblos

### **SECTION 8: Exposure controls/personal protection**

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton @ or Nitrile, thickness  $\ge 0.38$  mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended.

Recommended gloves: Nitrile, thickness ≥ 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

**Respiratory protection**: Based on the hazard and potential for exposure, select a respirator that meets the

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

**Environmental exposure** 

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

#### **Appearance**

Physical state : Liquid.
Color : White.

Odor : Characteristic.

Odor threshold : Not available.

Melting point/freezing point : Not available.

Boiling point, initial boiling point, and boiling range

Flammability : Not available.

Lower and upper explosion : Not available.

limit

limit

Flash point

: Not available.

Auto-ignition temperature :

Ingredient name	°C	°F	Method
sodium etasulfate	>400	>752	
tetrasodium N,N-bis(carboxylatomethyl)-L-glutamate	460	860	IEC 1241-2-1

**Decomposition temperature**: Not available.

**pH** : 10.6 [Conc. (% w/w): 100%] [DIN EN 1262]

Date of issue/Date of revision: 26-1-2024Version: 1Date of previous issue: 26-1-20248/16AkzoNobel

Fugen REINIGER 220 ml Farblos

### SECTION 9: Physical and chemical properties

Viscosity : Kinematic (room temperature): 74 mm²/s [DIN EN ISO 3219]

Kinematic (40°C): 20 mm<sup>2</sup>/s [DIN EN ISO 3219]

Solubility(ies) :

 Media
 Result

 cold water
 Soluble [OECD (TG 105)]

Partition coefficient: n-octanol/ : Not applicable.

water

Vapor pressure :

	Vapor Pressure at 20°C			Va	por pressur	e at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
sodium etasulfate	0.009	0.0012				

Relative density : 1.019

Vapor density : Not available.

Particle characteristics

Median particle size : Not applicable.

: 0

Percentage of particles with

aerodynamic diameter ≤ 10

μm

### **SECTION 10: Stability and reactivity**

**10.1 Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

**10.5 Incompatible materials** : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Date of issue/Date of revision: 26-1-2024Version: 1Date of previous issue: 26-1-20249/16AkzoNobel

Fugen REINIGER 220 ml Farblos

### **SECTION 11: Toxicological information**

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
sodium etasulfate	LD50 Dermal	Rabbit	6540 uL/kg	-
	LD50 Intraperitoneal	Rat	320 mg/kg	-
	LD50 Oral	Guinea pig	650 mg/kg	-
	LD50 Oral	Mouse	1550 mg/kg	-
	LD50 Oral	Rabbit	3580 mg/kg	-
	LD50 Oral	Rat	4 g/kg	-
	LD50 Subcutaneous	Rat	4730 mg/kg	-
trisodium nitrilotriacetate	LD50 Intraperitoneal	Rat	254 mg/kg	-
	LD50 Oral	Mouse	681 mg/kg	-
	LD50 Oral	Rat	1100 mg/kg	-

Conclusion/Summary

: Not available.

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
trisodium nitrilotriacetate	500	N/A	N/A	N/A	N/A

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
sodium etasulfate	Eyes - Mild irritant	Rabbit		250 ug	-
	Skin - Moderate irritant	Rabbit	-	500 mg	-

Conclusion/Summary

: Not available.

**Sensitization** 

**Conclusion/Summary**: Not available.

**Mutagenicity** 

**Conclusion/Summary**: Not available.

Carcinogenicity

**Conclusion/Summary**: Not available.

Reproductive toxicity

**Conclusion/Summary**: Not available.

**Teratogenicity** 

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Not available.

Date of issue/Date of revision: 26-1-2024Version: 1Date of previous issue: 26-1-202410/16

Fugen REINIGER 220 ml Farblos

### **SECTION 11: Toxicological information**

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.
 Skin contact : No known significant effects or critical hazards.
 Ingestion : No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion**: Adverse symptoms may include the following:

stomach pains

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Short term exposure**

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

#### Potential chronic health effects

Not available.

**Conclusion/Summary**: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

No additional information.

Date of issue/Date of revision: 26-1-2024Version: 1Date of previous issue: 26-1-202411/16

Fugen REINIGER 220 ml Farblos

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

Product/ingredient name	Result	Species	Exposure
trisodium nitrilotriacetate	Acute LC50 185000 µg/l Fresh water	Algae - Navicula seminulum	96 hours
	Acute LC50 477000 µg/l Fresh water	Algae - Navicula seminulum	96 hours
	Acute LC50 560000 to 1000000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 257000 µg/l Fresh water	Fish - Carassius auratus - Egg	96 hours
	Acute LC50 198000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 252000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 98000 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 127000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 100000 µg/l Fresh water	Algae - Algae - Exponential growth phase	96 hours
	Chronic NOEC 100000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 100000 µg/l Fresh water	Daphnia - Daphnia magna	21 days

**Conclusion/Summary**: Not available.

#### 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
trisodium nitrilotriacetate	-2.62	-	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility

: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

Date of issue/Date of revision: 26-1-2024Version: 1Date of previous issue: 26-1-202412/16AkzoNobel

Fugen REINIGER 220 ml Farblos

### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal**: The generation of waste should be avoided or minimized wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities

with jurisdiction.

Hazardous waste

: The classification of the product may meet the criteria for a hazardous waste.

**Disposal considerations** 

: Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 99	wastes not otherwise specified

#### **Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste

packaging should be recycled. Incineration or landfill should only be considered

when recycling is not feasible.

**Disposal considerations**: Using information provided in this safety data sheet, advice should be obtained from

the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or

national legal provisions.

**Special precautions**: This material and its container must be disposed of in a safe way. Care should be

taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

	ADR/RID	IMDG
14.1 UN number or ID number	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-
14.3 Transport hazard class(es)	-	-
14.4 Packing group	-	-
14.5 Environmental hazards	No.	No.

Date of issue/Date of revision	: 26-1-2024	Version :1	
Date of previous issue	: 26-1-2024	13/16	AkzoNobel

Fugen REINIGER 220 ml Farblos

### **SECTION 14: Transport information**

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not applicable.

### **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorization

#### **Annex XIV**

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions**: Not applicable.

on the manufacture. placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

VOC : Not available.

**VOC for Ready-for-Use** 

**Mixture** 

: Not applicable.

: Listed

Industrial emissions

(integrated pollution prevention and control) -

Air

**Industrial emissions** 

: Not listed

(integrated pollution prevention and control) -

Water

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### **Persistent Organic Pollutants**

Not listed.

#### **Seveso Directive**

This product is not controlled under the Seveso Directive.

#### **National regulations**

Product/ingredient name	List name	Name on list	Classification	Notes
		N,N-Bis (carboxymethyl)-glycin, Trinatrium-Salz	Carc. B	-

Date of issue/Date of revision : 26-1-2024 Version : 1 **AkzoNobel** Date of previous issue : 26-1-2024 14/16

Fugen REINIGER 220 ml Farblos

### **SECTION 15: Regulatory information**

**Biocidal products regulation** 

**Limitation of the use of :** Permitted.

organic solvents

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

15.2 Chemical Safety

Assessment

: No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information** 

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/20081

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Eye Dam. 1, H318	Calculation method	

#### Full text of abbreviated H statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.

#### Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4	
Carc. 2	CARCINOGENICITY - Category 2	
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
	_ ,	

Date of printing : 2-7-2024

Date of issue/Date of revision	: 26-1-2024	Version :1	
Date of previous issue	: 26-1-2024	15/16	AkzoNobel

Fugen REINIGER 220 ml Farblos

#### **SECTION 16: Other information**

Date of issue/ Date of

: 26-1-2024

revision

Date of previous issue : 26-1-2024

Version : 1

**Unique ID** : 7E46AA28D30B1EEEAF8DCB4C0147C8A4

#### **Notice to reader**

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision : 26-1-2024 Version : 1

16/16

Date of previous issue : 26-1-2024